

# FPFA-T Control Package

**FULLY AUTOMATIC CONTROL PACKAGE**



## PURPOSE

To fully automate the use of the **FLEXPAK™** Leak Detector, allow for recipe storage, repeatability and data acquisition

## VACUUM LEVELS

0-27 inches Hg (0-90 kPa) (to atmosphere)  
2.92 inches Hg (10 kPa) absolute

## ENCLOSURE

Stainless Steel

## OPERATOR INTERFACE

4.3 inch (11cm) Touch Screen

## CONTROL

Programmable Logic Controller (PLC)

## COMPRESSED AIR PRESSURE REQUIRED

70 psi (5 bar) minimum

## CONNECTION

¼ NPT; G ¼ adapter supplied outside North America

## POWER SUPPLY

120/230 VAC, 50/60 Hz, 1 Phase (power plug provided to suit country of destination)

## POWER REQUIRED

40 w

## APPROVALS

UL, CSA, CE according to EMC 2014/30EU and Low Voltage Directive 2014/35/EU

## Can be used for the following ASTM test procedures:

**ASTM D3078** Standard Test Method for Determination of Leaks in Flexible Packaging by Bubble Emission

**ASTM D6653** Standard Test Methods for Determining the Effects of High Altitude on Packaging Systems by Vacuum Method

**ASTM D4169** Standard Practice for Performance Testing of Shipping Containers and Systems

**ASTM D4991** Standard Test Method for Leakage Testing of Empty Rigid Containers by Vacuum Method

**ASTM D5094** Standard Test Method for Gross Leakage of Liquids from Containers with Threaded or Lug-Style Closures

**ASTM F2096** Standard Test Method for Gross Leakage of Liquids from Containers with Threaded or Lug-Style Closures

1.416.399.5583

[www.FlexPakInc.com](http://www.FlexPakInc.com) | [sales@FlexPakInc.com](mailto:sales@FlexPakInc.com)

**FLEXPAK™**

FlexPak Leak Detectors Inc.

380 Vansickle Road Unit 670, St. Catharines, ON L2S 0B5, Canada